## NSN 3020-00-823-9383



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-823-9383 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 1.3540 inches **Teeth Quantity:** 65 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end **Mounting Hole Thread Size:** 0.112 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 plain transversely through hub, first end and 1 threaded transversely through hub, first end **Outside Diameter:** 1.396 inches Nominallength: 0.310 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.185 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 

0.125 inches both ends

**Hub Style Designator:** 

Pinned first end

**Hub Diameter:** 

0.312 inches first end

**Mounting Hole Diameter:** 

0.040 inches transversely through hub, first end

Material:

Aluminum alloy 2024

**Material Specification:** 

Qq-a-250/4, t4 federal specification single material response

## NSN 3020-00-823-9383

Spur Gear - Page 2 of 2



_	•		_	-		
<b>ن</b>	ırfa	$\sim$	I ro	-atn	nor	٠.

Anodize

**Style Designator:** 

Protruding hub

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300