NSN 3020-00-825-4676

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-825-4676 **Body Style:** Plain, solid **Pitch Diameter:** Between 0.4677 inches and 0.4687 inches **Teeth Quantity:** 30 **Bore Style:** Plain both ends Hardness Rating: 75.0 rockwell b and 83.0 rockwell b **Outside Diameter:** 0.499 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.187 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.125 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.312 inches first end **Precision Classification:** Quality number 10 Material: Steel comp 302 and steel comp 302 **Material Specification:** Mil-s-7720, comp 302 military specification 1st material response and mil-s-7720, comp 303s military specification 2nd material response **Surface Treatment: Passivate Style Designator:** Protruding hub Shelf Life:

No

N/a

Unit Of Measure:

Demilitarization:

NSN 3020-00-825-4676

Spur Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-s-7720 spec.