## NSN 3020-00-828-2703

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-828-2703

Body Style:

| Body Style:   |
|---|
| Plain, solid  |
| Pitch Diameter:   |
| 1.5000 inches   |
| Teeth Quantity:   |
| 18  |
| Bore Style:   |
| 10a w/ keyway both ends   |
| Hardness Rating:  |
| 35.0 rockwell c   |
| Outside Diameter:   |
| 1.667 inches  |
| Tooth Form:   |
| Standard  |
| Pressure Angle:   |
| 20.0000 degrees   |
| Face Width:   |
| 1.125 inches  |
| Bore Diameter:  |
| 0.593 inches both ends  |
| Keyway Width:   |
| 0.127 inches both ends  |
| Distance From Bore Center To Keyway Bottom:                               |
| 0.368 inches both ends  |
| Precision Classification:   |
| Quality number 10   |
| Material:   |
| Steel comp 630  |
| Material Specification:   |
| Ams 5643, 17-4ph assn standard single material response                   |
| Surface Treatment:  |
| Passivate   |
| Surface Treatment Specification:  |
| Mil-f-14072, finish e300 military specification single treatment response |
| Style Designator:   |
| Hubless   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

## NSN 3020-00-828-2703

Spur Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-f-14072 spec.