## NSN 3020-00-834-7036

Spur Gear - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/3020-00-834-7036

Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
1.5270 inches
Teeth Quantity:
110
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
40 transversely through hub, first end
Hardness Rating:
75.0 rockwell c and 83.0 rockwell c
Mounting Hole Thread Size:
0.112 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end
Outside Diameter:
1.556 inches
Nominallength:
0.406 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.375 inches first end
Face Width:
0.187 inches
Bore Diameter:
0.188 inches both ends
Hub Style Designator:
Plain first end
Hub Diameter:
0.375 inches first end
Material:
Steel comp 303 and steel comp 303se
Material Specification:

Mil-s-7720, comp 303s military specification 1st material response and mil-s-7720, comp 303se military specification 2nd material response

## NSN 3020-00-834-7036

Spur Gear - Page 2 of 2



Passivate
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300

Mil-std (military Standard):

Mil-s-7720 spec.

**Surface Treatment:**