NSN 3020-00-839-1497

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-839-1497

| Body Style: |
|---|
| Plain, solid |
| Attachment Method: |
| Clamp |
| Pitch Diameter: |
| Between 1.4982 inches and 1.5002 inches |
| Teeth Quantity: |
| 144 |
| Bore Style: |
| Plain both ends |
| Outside Diameter: |
| 1.520 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.297 inches first end |
| Face Width: |
| 0.062 inches |
| Bore Diameter: |
| 0.125 inches both ends |
| Hub Style Designator: |
| 1 step first end |
| End Length: |
| 0.172 inches first end |
| End Diameter: |
| 0.188 inches first end |
| First Step Length: |
| 0.120 inches first end |
| First Step Diameter: |
| 0.250 inches first end |
| Special Features: |
| Hub is split equally in four sections 0.025 in. W, 0.280 in. Lg |
| Material: |
| Aluminum alloy 2024 |
| Material Specification: |
| Qq-a-225/6, t4 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |

Mil-a-8625 military specification single treatment response

NSN 3020-00-839-1497

Spur Gear - Page 2 of 2



| Style Designator: |
|-------------------|
| Protruding hub |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A27300 |

Mil-std (military Standard):

Mil-a-8625 spec.