## NSN 3020-00-839-8976

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-839-8976

**Body Style:** Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 2.0833 inches **Teeth Quantity:** 150 **Bore Style:** Plain both ends **Backlash Designation:** Grade c Mounting Hole Thread Series Designator: Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end Mounting Hole Thread Size: 0.112 inches transversely through hub, first end Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end **Outside Diameter:** 2.111 inches Nominallength: 0.343 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.218 inches first end Face Width: 0.125 inches **Bore Diameter:** 0.187 inches both ends Hub Style Designator: Pinned first end Hub Diameter: 0.375 inches first end **Precision Classification:** Quality number 10 or quality number 11 Material:

Steel comp 303

## NSN 3020-00-839-8976

Spur Gear - Page 2 of 2



## Material Specification:

Qq-s-763, class303 federal specification single material response

Surface Treatment:

Passivate

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300