NSN 3020-00-842-5789

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-842-5789

| Body Style: |
|--|
| Webbed, solid |
| Pitch Diameter: |
| Between 1.7215 inches and 1.7222 inches |
| Teeth Quantity: |
| 62 |
| Bore Style: |
| Plain both ends |
| Backlash Designation: |
| Grade c |
| Hardness Rating: |
| 38.0 rockwell c and 45.0 rockwell c |
| Outside Diameter: |
| 1.777 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.060 inches both ends |
| Face Width: |
| 0.330 inches |
| Bore Diameter: |
| 0.875 inches both ends |
| Hub Style Designator: |
| Plain both ends |
| Hub Diameter: |
| 1.000 inches both ends |
| Precision Classification: |
| Quality number 12 |
| Material: |
| Steel comp 630 |
| Material Specification: |
| Ams 5643 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Style Designator: |
| Protruding hubs |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 3020-00-842-5789

Spur Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300