## NSN 3020-00-846-3180

Spur Gear - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/3020-00-846-3180

## Body Style:

Plain, solid

**Attachment Method:** 

Mounting hole

## Pitch Diameter:

Between 0.8320 inches and 0.8330 inches

## **Teeth Quantity:**

40

Bore Style:

Plain both ends

**Backlash Designation:** 

Grade c

Mounting Hole Thread Series Designator:

Unc transversely through hub, first end

Mounting Hole Thready Qty Per Inch (tpi):

32 transversely through hub, first end

#### Mounting Hole Thread Size:

0.138 inches transversely through hub, first end

#### Mounting Hole Type And Quantity:

1 plain transversely through hub, first end and 1 threaded transversely through hub, first end

## Outside Diameter:

0.874 inches

Nominallength:

0.437 inches

## **Tooth Form:**

Standard

#### Pressure Angle:

20.0000 degrees

#### Distance Between Body Face And Protruding Hub End:

0.250 inches first end

#### Face Width:

0.187 inches

#### **Bore Diameter:**

0.250 inches both ends

#### Hub Style Designator:

Pinned first end

## Hub Diameter:

0.500 inches first end

## **Precision Classification:**

Quality number 10

#### Mounting Hole Diameter:

0.086 inches transversely through hub, first end



# NSN 3020-00-846-3180

Spur Gear - Page 2 of 2



Special Features:
Mtg holes 90 degs apart
Material:
Steel comp 303
Material Specification:
Qq-s-764, type 303 federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35, type 2 federal specification single treatment response
Style Designator:
Protruding hub
Furnished Items And Quantity:
1 setscrew
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300