## NSN 3020-00-850-6498

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-850-6498

| Attachment Method:   |
|--|
| Mounting hole  |
| Pitch Diameter:  |
| 1.3750 inches  |
| Teeth Quantity:  |
| 165  |
| Bore Style:  |
| Plain both ends  |
| Backlash Designation:  |
| Grade d  |
| Mounting Hole Thready Qty Per Inch (tpi):                      |
| 56 transversely through hub, first end                         |
| Mounting Hole Thread Size:                                     |
| 0.086 inches transversely through hub, first end               |
| Mounting Hole Type And Quantity:                               |
| 1 threaded transversely through hub, first end                 |
| Outside Diameter:  |
| 1.392 inches   |
| Tooth Form:  |
| Standard   |
| Pressure Angle:  |
| 20.0000 degrees  |
| Distance Between Body Face And Protruding Hub End:             |
| 0.250 inches first end   |
| Face Width:  |
| 0.125 inches   |
| Bore Diameter:   |
| 0.125 inches both ends   |
| Hub Style Designator:  |
| Plain first end  |
| Hub Diameter:  |
| 0.375 inches first end   |
| Precision Classification:                                      |
| Quality number 10  |
| Material:  |
| Steel comp 303se hub   |
| Material Specification:  |
| Qq-a-225/6 federal specification single material response body |
| Surface Treatment:   |
| Passivate hub  |
| Style Designator:  |
| Protruding hub   |
|  |

## NSN 3020-00-850-6498

Spur Antibacklash Gear - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

## Mil-std (military Standard):

Mil-s-7720 spec.

