## NSN 3020-00-850-9953

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-850-9953

**Body Style:** Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 1.3750 inches **Teeth Quantity:** 66 **Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unc axially through body, first end Mounting Hole Thready Qty Per Inch (tpi): 32 axially through body, first end Mounting Hole Thread Size: 0.164 inches axially through body, first end Mounting Hole Type And Quantity: 3 threaded axially through body, first end **Outside Diameter:** 1.416 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.437 inches first end Face Width: 0.125 inches **Bore Diameter:** 0.625 inches both ends Hub Style Designator: 1 step first end End Length: 0.125 inches first end End Diameter: 0.749 inches first end First Step Length: 0.312 inches first end **First Step Diameter:** 1.312 inches first end **Bolt Hole Circle Diameter:** 1.000 inches axially through body, first end

# NSN 3020-00-850-9953

Spur Gear - Page 2 of 2



Material:

Aluminum alloy 2024

### Material Specification:

Qq-a-225/6, t4 federal specification single material response

#### Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A27300