

View Online at <https://aerobasegroup.com/nsn/3020-00-851-2384>

Groove Depth:

0.430 inches

Groove Width:

0.380 inches

Outside Diameter:

5.520 inches

Overall Length:

3.020 inches

Keyway Width:

Between 0.251 inches and 0.253 inches

Bore Diameter:

1.245 inches

Bore Length:

1.200 inches

Distance From Center Of Bore To Bottom Of Keyway:

0.741 inches

V Groove Angle In Deg:

36.0

Pitch Diameter:

5.400 inches

Material And Location:

Iron, cast, qq-i-652, class 30

Face Width:

2.140 inches

Design Form:

Webbed

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

4

Counterbore Feature:

Not included

Keying Facility:

Included

Keying Facility Type:

Integral key

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Not offset

Lightening Hole:

Included

Integral Cooling Vane:

Not included

Groove Shape:

V

Standard V-belt Section Designation For Which Designed:

A

Bore Feature:

Included

Hub End Outside Diameter And Location:

1.750 inches both ends

Distance From Outside Flange/rim To Hub End And Location:

0.880 inches both ends

Quantity:

1

Surface Treatment:

Phosphate and enamel semigloss

Surface Treatment Specification:

Mil-c-490 military specification 1st treatment response and tt-e-529 finish federal specification 2nd treatment response

Style Designator:

Webbed or spoked

Surface Treatment:

Phosphate coat, grade 1, spec mil-c-490 and enamel o.D. Per specification tt-e-529 finish

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a

Mil-std (military Standard):

Mil-c-490 spec.