NSN 3020-00-852-7379



Sprocket Wheel - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-852-7379 **Outside Diameter:** 2.640 inches **Overall Length:** 0.840 inches **Thread Size:** 1/4 in.-20 **Bore Diameter:** 0.4390 inches **Bore Length:** 0.840 inches Pitch Diameter: 2.400 inches **Securing Hole Quantity:** 1 or 1 **Face Width:** 0.168 inches Guide: Not included **Design Form:** Plain **Bore Type:** Straight **Counterbore Feature:** Not included **Hole Location:** Located on hub portion of gear between hub end and face; located 90 degrees from thd hole **Keying Facility:** Not included **Securing Method:** Threaded hole **Lightening Hole:** Not included **Protruding Hub Characteristic:** Plain **Securing Location:** Aa end Err Default: Err default

Belt/chain/film Size For Which Designed: Roller chain

Roller Chain Pitch Type For Which Designed:

Single pitch

NSN 3020-00-852-7379 Sprocket Wheel - Page 2 of 2



Feeth Row Quantity:
1
Teeth Quantity Per Row:
20
Asa Standard Chain Number:
35
Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Footh Pitch:
0.375 inches
Hub End Outside Diameter And Location:
1.840 inches both ends
Distance From Outside Flange/rim To Hub End And Location:
0.672 inches both ends
Material:
Steel, qq-s-633, fs1010-canceled or steel, qq-s-633, fs1020-canceled
Material:
Steel comp 1010 or steel comp 1020
Material Specification:
Qq-s-633, fs1010-canceled federal specification 1st material response and qq-s-633, fs1020-canceled federal specification 2nd material
response
Style Designator:
Plain
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No No
Filg:
Г353-с