NSN 3020-00-854-0958

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-854-0958

Body Style:
Plain, solid
Pitch Diameter:
0.8750 inches
Teeth Quantity:
56
Bore Style:
Plain both ends
Backlash Designation:
Grade b
Outside Diameter:
0.900 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.250 inches first end
Face Width:
0.093 inches
Bore Diameter:
0.125 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
0.125 inches first end
Precision Classification:
Quality number 10
Material:
Aluminum alloy
Admindmanoy
Material Specification:
•
Material Specification:
Material Specification: Qq-a-225 federal specification single material response
Material Specification: Qq-a-225 federal specification single material response Surface Treatment:
Material Specification: Qq-a-225 federal specification single material response Surface Treatment: Anodize
Material Specification: Qq-a-225 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification:
Material Specification: Qq-a-225 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response
Material Specification: Qq-a-225 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Style Designator:
Material Specification: Qq-a-225 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Style Designator: Protruding hub

--

NSN 3020-00-854-0958

Spur Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.