NSN 3020-00-857-5695

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-857-5695

| view Online at https://aerobasegroup.com/nsn/3020-00-657-5695 |
|---|
| Outside Diameter: |
| 3.938 inches |
| Overall Length: |
| 1.000 inches |
| Keyway Width: |
| 0.09375 inches |
| Bore Diameter: |
| 1.625 inches |
| Bore Length: |
| 1.000 inches |
| Distance From Center Of Bore To Bottom Of Keyway: |
| 1.000 inches |
| Pitch Diameter: |
| 3.672 inches |
| Taper Bore Major Diameter: |
| 1.625 inches |
| Face Width: |
| 0.7969 inches |
| Design Form: |
| Plain |
| Bore Type: |
| Straight |
| Counterbore Feature: |
| Not included |
| Keying Facility: |
| Included |
| Keying Facility Type: |
| Keyway |
| Lightening Hole: |
| Not included |
| Protruding Hub Characteristic: |
| Plain |
| Belt/chain/film Size For Which Designed: |
| Roller chain |
| Roller Chain Pitch Type For Which Designed: |
| Single pitch |
| Teeth Row Quantity: |
| 2 |
| Center To Center Distance Between Teeth Rows: |
| 0.500 inches |
| Teeth Quantity Per Row: |
| |

23

NSN 3020-00-857-5695

Sprocket Wheel - Page 2 of 2



Asa Standard Chain Number: 40-2 Hardness Rating Test Method: Not rated **Bore Bearing:** Not included Hub External Keyway: Not included **Tooth Pitch:** 0.500 inches Hub End Outside Diameter And Location: 3.140625 inches both ends Distance From Outside Flange/rim To Hub End And Location: 0.2031 inches both ends Material: Steel, corrosion resisting Material: Stainless steel Quantity: 1 **Surface Treatment:** Passivate Style Designator: Plain Surface Treatment: Passivated Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: T353-c