## NSN 3020-00-859-2554

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-859-2554 **Attachment Method:** Mounting hole Pitch Diameter: 4.0000 inches **Teeth Quantity:** 192 **Bore Style:** Plain both ends **Mounting Hole Type And Quantity:** 2 plain transversely through hub, first end **Outside Diameter:** 4.042 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.125 inches first end **Face Width:** 0.183 inches **Bore Diameter:** 0.218 inches both ends **Hub Style Designator:** Plain both ends **Hub Diameter:** 0.875 inches first end **Mounting Hole Diameter:** 0.110 inches transversely through hub, first end Material: Steel spring **Material Specification:** Qq-a-250/4, t3 federal specification single material response second gear **Surface Treatment:** Passivate hub **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response second gear **Style Designator:** Protruding hubs Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 3020-00-859-2554

Spur Antibacklash Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-7720 spec.