NSN 3020-00-859-2554

Spur Antibacklash Gear - Page 1 of 2



Spur Antibacklash Gear - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/3020-00-859-2554
Attachment Method:
Mounting hole
Pitch Diameter:
4.0000 inches
Teeth Quantity:
192
Bore Style:
Plain both ends
Mounting Hole Type And Quantity:
2 plain transversely through hub, first end
Outside Diameter:
4.042 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.125 inches first end
Face Width:
0.183 inches
Bore Diameter:
0.218 inches both ends
Hub Style Designator:
Plain both ends
Hub Diameter:
0.875 inches first end
Mounting Hole Diameter:
0.110 inches transversely through hub, first end
Material:
Steel spring
Material Specification:
Qq-a-250/4, t3 federal specification single material response second gear
Surface Treatment:
Passivate hub
Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response second gear

Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

NSN 3020-00-859-2554

Spur Antibacklash Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-7720 spec.