## NSN 3020-00-862-5570

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-862-5570 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 3.8333 inches **Teeth Quantity:** 184 **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 32 transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 3.875 inches Nominallength: 0.375 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.250 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.250 inches both ends **End Length:** 0.187 inches first end **Precision Classification:** Quality number 10 or quality number 11 **End Diameter:** 0.500 inches first end First Step Length: 0.063 inches first end First Step Diameter: 0.875 inches first end Material: Aluminum alloy 2024

Material Specification:

Qq-a-225/6 federal specification single material response

## NSN 3020-00-862-5570

Spur Gear - Page 2 of 2

Mil-a-8625 spec.



Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 1 military specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):