# NSN 3020-00-862-5570

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-862-5570

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
3.8333 inches
Teeth Quantity:
184
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
32 transversely through hub, first end
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end
Outside Diameter:
3.875 inches
Nominallength:
0.375 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.250 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.250 inches both ends
End Length:
0.187 inches first end
Precision Classification:
Quality number 10 or quality number 11
End Diameter:
0.500 inches first end
First Step Length:
0.063 inches first end
First Step Diameter:
0.875 inches first end
Material:
Aluminum alloy 2024
Material Specification:

Qq-a-225/6 federal specification single material response

# NSN 3020-00-862-5570

Spur Gear - Page 2 of 2



Surface Treatment:

Anodize

#### Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

#### Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A27300

## Mil-std (military Standard):

Mil-a-8625 spec.