# NSN 3020-00-863-5620

Spur Gear Sector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-863-5620

#### Attachment Method:

Mounting hole

#### **End Application:**

M110 howitzer family

#### Teeth Quantity:

24

#### Pitch Radius:

28.7500 inches

#### Mounting Hole Type And Quantity:

2 counterbored transversely through flange and 2 plain transversely through flange

#### Tooth Form:

Stub

#### Pressure Angle:

20.0000 degrees

#### Face Width:

6.000 inches

## Outside Radius:

29.900 inches

## Arc Length:

34.750 inches

#### Mounting Hole Diameter:

1.310 inches transversely through flange and 1.560 inches transversely through flange

#### **Special Features:**

2 other mtg holes 1.060 diameter 8.500c-to-c 2.880 from one end

Material:

Steel comp 105-85

#### **Material Specification:**

Qq-s-681 cl 105-85 federal specification single material response

#### Surface Treatment:

Phosphate manganese

#### Surface Treatment Specification:

Mil-p-16232 ty m cl 2 military specification single treatment response

#### Style Designator:

Plain ring

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

#### Fiig:

A27300

# NSN 3020-00-863-5620

Spur Gear Sector - Page 2 of 2

### Mil-std (military Standard):

Mil-p-16232 spec.

