NSN 3020-00-866-8030

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-866-8030

Body Style:					
Plain, with lightening holes					
Pitch Diameter:					
0.6560 inches					
Teeth Quantity:					
21					
Bore Style:					
D both ends					
Hardness Rating:					
33.0 rockwell c and 43.0 rockwell c					
Outside Diameter:					
0.745 inches					
Nominallength:					
1.700 inches					
Tooth Form:					
Standard					
Pressure Angle:					
20.0000 degrees					
Distance Between Body Face And Protruding Hub End:					
0.532 inches first end					
Face Width:					
0.760 inches					
Radius:					
0.194 inches both ends					
Distance From Flat To Radial Center:					
0.136 inches both ends					
Counterbore Depth:					
4.440 in all a a la atha an ala					
1.440 inches both ends					
Counterbore Diameter:					
Counterbore Diameter:					
Counterbore Diameter: 0.411 inches both ends					
Counterbore Diameter: 0.411 inches both ends Hub Style Designator:					
Counterbore Diameter: 0.411 inches both ends Hub Style Designator: Plain both ends					
Counterbore Diameter: 0.411 inches both ends Hub Style Designator: Plain both ends Hub Diameter:					
Counterbore Diameter: 0.411 inches both ends Hub Style Designator: Plain both ends Hub Diameter: 0.532 inches second end					
Counterbore Diameter: 0.411 inches both ends Hub Style Designator: Plain both ends Hub Diameter: 0.532 inches second end Precision Classification:					
Counterbore Diameter: 0.411 inches both ends Hub Style Designator: Plain both ends Hub Diameter: 0.532 inches second end Precision Classification: Quality number 10 or quality number 11					
Counterbore Diameter: 0.411 inches both ends Hub Style Designator: Plain both ends Hub Diameter: 0.532 inches second end Precision Classification: Quality number 10 or quality number 11 Material:					

Style Designator: Protruding hubs

NSN 3020-00-866-8030

Spur Gear - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300