## NSN 3020-00-868-9825

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-868-9825

**Body Style:** Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 9.2500 inches **Teeth Quantity:** 74 **Bore Style:** W/stepped counterbore second end Mounting Hole Thread Series Designator: Unc transversely through hub, first end Hardness Rating: 58.0 rockwell c teeth and 62.0 rockwell c teeth Mounting Hole Thread Size: 0.375 inches transversely through hub, first end Mounting Hole Type And Quantity: 2 plain axially through body, second end **Outside Diameter:** 9.449 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 3.687 inches first end Face Width: 1.125 inches **Bore Diameter:** 2.875 inches both ends **Counterbore Depth:** 3.188 inches counterbore, first end **Counterbore Diameter:** 5.500 inches first counterbore, second end Hub Style Designator: Plain first end Hub Diameter: 4.875 inches first end Mounting Hole Diameter: 0.562 inches axially through body, second end **Special Features:** Slotted counterbore, second end; 0.125 in wide, 1.750 in. From end

# NSN 3020-00-868-9825

Spur Gear - Page 2 of 2



Material:

Steel comp 4620

### Material Specification:

Fed standard 66 federal standard single material response

#### Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

#### Demilitarization:

No

#### Fiig:

A27300