
# NSN 3020-00-869-7310

Spur Gear - Page 1 of 2



#### **Body Style:**

Plain, solid

#### **Attachment Method:**

Clamp

## **Pitch Diameter:**

Between 1.6657 inches and 1.6667 inches

## **Teeth Quantity:**

160

Bore Style:

Plain both ends

#### **Backlash Designation:**

Grade c

#### Outside Diameter:

1.687 inches

#### **Tooth Form:**

Standard

# Pressure Angle:

20.0000 degrees

# Distance Between Body Face And Protruding Hub End:

0.264 inches first end

# Face Width:

0.125 inches

## Bore Diameter:

0.121 inches both ends

#### Hub Style Designator:

Split first end

## Hub Diameter:

0.375 inches first end

#### Clamping Surface Length:

0.234 inches first end

#### **Precision Classification:**

Quality number 10 or quality number 11

#### Material:

Aluminum alloy 2024

#### **Material Specification:**

Qq-a-225/6, t4 federal specification single material response

## Surface Treatment:

Anodize

## Style Designator:

Protruding hub

## Shelf Life:

N/a



# NSN 3020-00-869-7310

Spur Gear - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

