## NSN 3020-00-871-2831

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-871-2831

Body Style:
Plain, solid
Spline Quantity:
6 first end
Attachment Method:
Mounting hole
Pitch Diameter:
4.5000 inches
Teeth Quantity:
15
Bore Style:
Straight spline first end
Mounting Hole Thread Series Designator:
Unf axially through body, first end
Hardness Rating:
58.0 rockwell c and 62.0 rockwell c
Mounting Hole Thread Size:
0.250 inches axially through body, first end
Mounting Hole Type And Quantity:
6 threaded axially through body, first end
Outside Diameter:
3.666 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.750 inches first end
Face Width:
1.375 inches
Bore Diameter:
1.165 inches first end
Hub Style Designator:
Externally splined, involute splines first end
Hub Spline Quantity:
15 first end
Hub Spline Pitch Diameter:
3.3333 inches first end
Special Features:
Counterbore second end, 1.903 in. Dia, 0.313 in. Deep
Material:
Steel

## NSN 3020-00-871-2831

Spur Gear - Page 2 of 2

Mil-std (military Standard):

Mil-p-16232 spec.



Surface Treatment:
Phosphate
Surface Treatment Specification:
Mil-p-16232, type m, class 2 military specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300