# NSN 3020-00-874-0769

Spur Gear - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/3020-00-874-0769



# Body Style:

Plain, solid

# **Spline Quantity:**

24 both ends

# Pitch Diameter:

Between 3.3620 inches and 3.3720 inches

### **Teeth Quantity:**

31

#### Bore Style:

Involute spline both ends

### Spline Pitch Diameter:

1.2000 inches both ends

### **Outside Diameter:**

3.539 inches

# Pressure Angle:

20.0000 degrees

#### Face Width:

1.690 inches

# **Bore Diameter:**

1.273 inches both ends

# Hub Style Designator:

3 steps first end

# End Length:

1.198 inches first end

#### End Diameter:

1.969 inches second end

#### First Step Length:

0.770 inches first end

# First Step Diameter:

2.500 inches second end

#### Second Step Length:

1.200 inches first end

#### Second Step Diameter:

2.500 inches first end

#### Third Step Diameter:

2.088 inches first end

#### **Special Features:**

Internal relief on bore 1.5000in. From first end length of relief 2.5400in. Dia. Of relief equal todimensions of counterbore second end dia.1.500in.; depth 0.120in.

# Material:

Steel comp 8620

# **Material Specification:**

Mil-s-8690 military standard single material response

# NSN 3020-00-874-0769

Spur Gear - Page 2 of 2

Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-8690 spec.

