NSN 3020-00-876-7880

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-876-7880 **Body Style:** Plain, solid **Attachment Method:** Mounting hole **Teeth Quantity:** 26 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc axially through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 axially through hub, first end **Mounting Hole Type And Quantity:** 2 threaded axially through hub, first end **Outside Diameter:** 0.500 inches Nominallength: 0.330 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.180 inches first end Face Width: 0.150 inches **Hub Style Designator:** Plain first end Material: Aluminum alloy Surface Treatment:

ourrace freatment.
Anodize
Surface Treatment Specification:
Mil-s-8625 military specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

NSN 3020-00-876-7880

Spur Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-s-8625 spec.