## NSN 3020-00-876-7880

Spur Gear - Page 1 of 2



-00-876-7880

View Online at https://aerobasegroup.com/nsn/3020-00-876-
Body Style:
Plain, solid
Attachment Method:
Mounting hole
Teeth Quantity:
26
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc axially through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
56 axially through hub, first end
Mounting Hole Type And Quantity:
2 threaded axially through hub, first end
Outside Diameter:
0.500 inches
Nominallength:
0.330 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.180 inches first end
Face Width:
0.150 inches
Hub Style Designator:
Plain first end
Material:
Aluminum alloy
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-s-8625 military specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Yes - demil/mli

## NSN 3020-00-876-7880

Spur Gear - Page 2 of 2

Fiig: A27300 Mil-std (military Standard):

Mil-s-8625 spec.

