NSN 3020-00-881-0659

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-881-0659

Outside Diameter:

1.088 inches

Overall Length:

0.375 inches

Thread Size:

No.6-32

Bore Diameter:

0.315 inches

Bore Length:

0.375 inches

Drilled Hole Diameter:

0.070 inches

Pitch Diameter:

1.036 inches

Securing Hole Quantity:

1 or 1

Furnished Items And Quantity:

Setscrew 1

Face Width:

0.125 inches

Guide:

Not included

Design Form:

Plain

Bore Type:

Straight

Counterbore Feature:

Not included

Hole Location:

0.120 in. From end of hub; located 90 degrees from thd hole

Keying Facility:

Not included

Securing Method:

Threaded hole or drilled hole

Lightening Hole:

Not included

Protruding Hub Characteristic:

Plain

Securing Location:

Aa end

Belt/chain/film Size For Which Designed:

Roller chain

NSN 3020-00-881-0659

Sprocket Wheel - Page 2 of 2



Roller Chain Pitch Type For Which Designed:

Single pitch

Teeth Row Quantity:

1

Teeth Quantity Per Row:

22

Hardness Rating Test Method:

Not rated

Bore Bearing:

Not included

Hub External Keyway:

Not included

Tooth Pitch:

0.1475 inches

Hub End Outside Diameter And Location:

0.500 inches both ends

Distance From Outside Flange/rim To Hub End And Location:

0.250 inches both ends

Material:

Steel, mil-s-7720, comp 303s or steel, mil-s-7720, comp 303se

Material:

Steel comp 303 or steel comp 303se

Material Specification:

Mil-s-7720, comp 303s military specification 1st material response and mil-s-7720, comp 303se military specification 2nd material response

Surface Treatment:

Passivate

Style Designator:

Plain

Surface Treatment:

Passivated

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

Т353-с

Mil-std (military Standard):

Mil-s-7720 spec.