## NSN 3020-00-884-1208

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-884-1208 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 1.6880 inches **Teeth Quantity:** 27 **Bore Style:** 10a w/ keyway both ends **Mounting Hole Thread Series Designator:** Unf transversely through hub, first end **Hardness Rating:** 28.0 rockwell c and 36.0 rockwell c **Mounting Hole Thread Size:** 0.190 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 1.8105 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.3500 inches first end **Face Width:** 0.470 inches **Bore Diameter:** 0.6260 inches both ends **Keyway Width:** 0.1910 inches both ends **Distance From Bore Center To Keyway Bottom:** 0.3990 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 1.2500 inches first end Material:

Steel comp 4140

**Material Specification:** 

Fed standard 66 federal standard single material response

## NSN 3020-00-884-1208

Spur Gear - Page 2 of 2



	Trea	

Passivate

**Style Designator:** 

Protruding hub

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300