NSN 3020-00-887-2664

Spur Gear - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/3020-00-887-2664

,						
Attachment Method:						
Mounting hole						
Pitch Diameter:						
1.0000 inches						
Teeth Quantity:						
120						
Bore Style:						
Plain both ends						
Mounting Hole Thread Series Designator:						
Unf transversely through hub, first end						
Mounting Hole Thready Qty Per Inch (tpi):						
80 transversely through hub, first end						
Mounting Hole Thread Size:						
0.060 inches transversely through hub, first end						
Mounting Hole Type And Quantity:						
2 threaded transversely through hub, first end						
Outside Diameter:						
1.017 inches						
Nominallength:						
Hommanengur.						
0.259 inches						
0.259 inches						
0.259 inches Tooth Form:						
0.259 inches Tooth Form: Standard						
0.259 inches Tooth Form: Standard Pressure Angle:						
0.259 inches Tooth Form: Standard Pressure Angle: 20.0000 degrees						
0.259 inches Tooth Form: Standard Pressure Angle: 20.0000 degrees Distance Between Body Face And Protruding Hub End:						
0.259 inches Tooth Form: Standard Pressure Angle: 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.187 inches first end						
0.259 inches Tooth Form: Standard Pressure Angle: 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.187 inches first end Face Width:						
0.259 inches Tooth Form: Standard Pressure Angle: 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.187 inches first end Face Width: 0.072 inches						
0.259 inches Tooth Form: Standard Pressure Angle: 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.187 inches first end Face Width: 0.072 inches Bore Diameter:						
0.259 inches Tooth Form: Standard Pressure Angle: 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.187 inches first end Face Width: 0.072 inches Bore Diameter: 0.078 inches both ends						
0.259 inches Tooth Form: Standard Pressure Angle: 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.187 inches first end Face Width: 0.072 inches Bore Diameter: 0.078 inches both ends Hub Style Designator:						
0.259 inches Tooth Form: Standard Pressure Angle: 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.187 inches first end Face Width: 0.072 inches Bore Diameter: 0.078 inches both ends Hub Style Designator: Pinned first end						
0.259 inches Tooth Form: Standard Pressure Angle: 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.187 inches first end Face Width: 0.072 inches Bore Diameter: 0.078 inches both ends Hub Style Designator: Pinned first end Hub Diameter:						
0.259 inches Tooth Form: Standard Pressure Angle: 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.187 inches first end Face Width: 0.072 inches Bore Diameter: 0.078 inches both ends Hub Style Designator: Pinned first end Hub Diameter: 0.212 inches first end						

Material Specification:

Steel comp 416

material opcomoditori.

Qq-s-763, class 416, cond a federal specification single material response

NSN 3020-00-887-2664

Spur Gear - Page 2 of 2



_	•	_				
<u>ن</u>	urfac	ו סי	roo:	ŀm.	Δn	٠.
J	ui iav	<i>,</i> – ,	ıca		CII	L.

Passivate

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300