

View Online at <https://aerobasegroup.com/nsn/3020-00-889-5604>

Groove Depth:

0.625 inches

Groove Width:

0.652 inches

Outside Diameter:

4.800 inches

Overall Length:

2.375 inches

Keyway Width:

Between 0.249 inches and 0.251 inches

Bore Diameter:

Between 0.125 inches and 0.126 inches

Bore Length:

1.625 inches

Distance From Center Of Bore To Bottom Of Keyway:

Between 1.250 inches and 1.255 inches

V Groove Angle In Deg:

34.0

Pitch Diameter:

4.400 inches

Furnished Items And Quantity:

7/16 in. Lg self-locking cup-pt, 2 places on hub

Material And Location:

Iron, cast, qq-i-652, class 20

Face Width:

1.750 inches

Design Form:

Webbed

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

2

Counterbore Feature:

Not included

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Setscrew

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Offset

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

V

Standard V-belt Section Designation For Which Designed:

5I

Bore Feature:

Included

Protruding Hub Characteristic:

Plain

Securing Location:

Aa end

Hub End Outside Diameter And Location:

2.500 inches aa end

Distance From Outside Flange/rim To Hub End And Location:

0.625 inches aa end and 0.750 inches bb end

Quantity:

1

Surface Treatment:

Painted dark machinery gray

Style Designator:

Webbed or spoked

Surface Treatment:

Painted dark machinery gray

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a