

View Online at <https://aerobasegroup.com/nsn/3020-00-889-5604>

**Groove Depth:**

0.625 inches

**Groove Width:**

0.652 inches

**Outside Diameter:**

4.800 inches

**Overall Length:**

2.375 inches

**Keyway Width:**

Between 0.249 inches and 0.251 inches

**Bore Diameter:**

Between 0.125 inches and 0.126 inches

**Bore Length:**

1.625 inches

**Distance From Center Of Bore To Bottom Of Keyway:**

Between 1.250 inches and 1.255 inches

**V Groove Angle In Deg:**

34.0

**Pitch Diameter:**

4.400 inches

**Furnished Items And Quantity:**

7/16 in. Lg self-locking cup-pt, 2 places on hub

**Material And Location:**

Iron, cast, qq-i-652, class 20

**Face Width:**

1.750 inches

**Design Form:**

Webbed

**Bore Type:**

Straight

**Bearings:**

Not included

**Groove Quantity:**

2

**Counterbore Feature:**

Not included

**Keying Facility:**

Included

**Keying Facility Type:**

Keyway

**Securing Method:**

Setscrew

**Split Hub Feature:**

Not included

**Web/spoke Relationship To Face Centerline:**

Offset

**Lightening Hole:**

Not included

**Integral Cooling Vane:**

Not included

**Groove Shape:**

V

**Standard V-belt Section Designation For Which Designed:**

5I

**Bore Feature:**

Included

**Protruding Hub Characteristic:**

Plain

**Securing Location:**

Aa end

**Hub End Outside Diameter And Location:**

2.500 inches aa end

**Distance From Outside Flange/rim To Hub End And Location:**

0.625 inches aa end and 0.750 inches bb end

**Quantity:**

1

**Surface Treatment:**

Painted dark machinery gray

**Style Designator:**

Webbed or spoked

**Surface Treatment:**

Painted dark machinery gray

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T353-a