# NSN 3020-00-890-2257

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-890-2257

# Body Style:

Plain, solid

# **Attachment Method:**

Mounting hole

# Pitch Diameter:

Between 1.8743 inches and 1.8750 inches

# **Teeth Quantity:**

120

## Bore Style:

Plain both ends

### Mounting Hole Thread Series Designator:

Unc transversely through hub, first end

# Mounting Hole Thready Qty Per Inch (tpi):

56 transversely through hub, first end

### Mounting Hole Thread Size:

0.086 inches transversely through hub, first end

# Mounting Hole Type And Quantity:

1 plain transversely through hub, first end and 1 threaded transversely through hub, first end

#### Outside Diameter:

1.905 inches

# Nominallength:

0.312 inches

# Tooth Form:

Standard

#### Pressure Angle:

20.0000 degrees

# Distance Between Body Face And Protruding Hub End:

0.187 inches first end

# Face Width:

0.125 inches

#### Bore Diameter:

0.125 inches both ends

#### Hub Style Designator:

Pinned first end

#### Hub Diameter:

0.312 inches first end

# **Precision Classification:**

Quality number 12

# Mounting Hole Diameter:

0.029 inches transversely through hub, first end

# **Special Features:**

Unthreaded hole 90 degrees from threaded hole

# NSN 3020-00-890-2257

Spur Gear - Page 2 of 2



# Material:

Aluminum alloy 2024

# **Material Specification:**

Qq-a-225/6, t4 federal specification single material response

### Surface Treatment:

Anodize

# Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

# Style Designator:

Protruding hub

Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A27300

# Mil-std (military Standard):

Mil-a-8625 spec.