NSN 3020-00-891-4293

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-891-4293

| Body Style: |
|---|
| Plain, solid |
| Pitch Diameter: |
| Between 1.2490 inches and 1.2500 inches |
| Teeth Quantity: |
| 60 |
| Bore Style: |
| Plain both ends |
| Outside Diameter: |
| 1.291 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.187 inches first end |
| Face Width: |
| 0.125 inches |
| Bore Diameter: |
| 0.125 inches both ends |
| Hub Style Designator: |
| Pinned first end |
| Hub Diameter: |
| 0.312 inches first end |
| Precision Classification: |
| Quality number 10 or quality number 11 |
| Material: |
| Aluminum alloy 2024 |
| Material Specification: |
| Qq-a-225/6, t4 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625, type 1 military specification single treatment response |
| Style Designator: |
| Protruding hub |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 3020-00-891-4293

Spur Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.