NSN 3020-00-893-8310

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-893-8310 **Body Style:** Plain, solid **Attachment Method:** Mounting hole **Serration Quantity:** 23 both ends Pitch Diameter: 1.5000 inches **Teeth Quantity:** 24 **Bore Style:** Serrated both ends **Serration Pitch Diameter:** 0.7188 inches both ends Hardness Rating: 58.0 rockwell c and 63.0 rockwell c **Mounting Hole Type And Quantity:** 2 plain transversely through hub, first end **Outside Diameter:** 1.615 inches Nominallength: 0.873 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.300 inches first end **Face Width:** 0.562 inches **Hub Style Designator:** Pinned first end **Hub Diameter:** 1.000 inches first end **Precision Classification:** Quality number 9 **Mounting Hole Diameter:** 0.096 inches transversely through hub, first end Material: Steel

Material Specification:

Qq-s-624 federal specification single material response

NSN 3020-00-893-8310

Spur Gear - Page 2 of 2



$\overline{}$			-			
~ I	ırfa	ഫ	ırc	natr	nΔn	

Passivate

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A27300