## NSN 3020-00-897-8593

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-897-8593

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
3.8333 inches
Teeth Quantity:
184
Bore Style:
W/counterbore counterbore, first end
Mounting Hole Type And Quantity:
4 plain axially through body, first end and 3 plain axially through body, first end
Outside Diameter:
3.875 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Face Width:
0.125 inches
Bore Diameter:
0.640 inches counterbore, first end
Counterbore Depth:
0.031 inches counterbore, first end
Counterbore Diameter:
1.255 inches counterbore, first end
Precision Classification:
Quality number 10 or quality number 11
Mounting Hole Diameter:
0.128 inches axially through body, first end and 0.177 inches axially through body, first end
Special Features:
Drilled holes 0.177 in. Diameter counterbored 7/16 in. By 1/16 in. Deep
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, t4 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 1 military specification single treatment response
Style Designator:
Hubless

## NSN 3020-00-897-8593

Spur Gear - Page 2 of 2



N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.