NSN 3020-00-899-4242

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-899-4242

View Online at https://aerobasegroup.com/nsn/3020-00-899-4242
Body Style:
Plain, with lightening holes
Attachment Method:
Mounting hole
Pitch Diameter:
2.5000 inches
Teeth Quantity:
60
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
32 transversely through hub, first end
Hardness Rating:
28.0 rockwell c and 32.0 rockwell c
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end
Nominallength:
0.625 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.438 inches first end
Face Width:
0.187 inches
Bore Diameter:
0.375 inches both ends
Hub Diameter:
0.750 inches first end
Special Features:
0.093 in. Spot drilled hole, located 90 degrees fromthreaded hole on hub
Material:
Steel comp 4140
Material Specification:
Qq-s-624 federal specification single material response
Surface Treatment:
Phosphate manganese
Surface Treatment Specification:
Mil-p-16232 type m, class 2 military specification single treatment response

Style Designator:

Protruding hub

NSN 3020-00-899-4242

Spur Gear - Page 2 of 2



Shelf	Life:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-p-16232 spec.