NSN 3020-00-899-4243

Spur Gear - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/3020-00-899-4243

Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
1.5417 inches
Teeth Quantity:
37
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
32 transversely through hub, first end
Hardness Rating:
28.0 rockwell c and 32.0 rockwell c
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end
Outside Diameter:
1.624 inches
Nominallength:
0.500 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.250 inches first end
Face Width:
0.250 inches
Bore Diameter:
0.375 inches both ends
Hub Diameter:
0.625 inches first end
Special Features:
Hole 0.093 in. Spot drilled 90 degree from threaded hole
Material:
Steel comp 4140
Material Specification:
Qq-s-624 federal specification single material response
Surface Treatment:
Phosphate manganese
Surface Treatment Specification:

Mil-p-16232 type m, class 2 military specification single treatment response

NSN 3020-00-899-4243

Spur Gear - Page 2 of 2



Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Deminitarization.
No

Mil-std (military Standard):

Mil-p-16232 spec.