

View Online at <https://aerobasegroup.com/nsn/3020-00-899-6713>

Groove Depth:

0.430 inches

Groove Width:

0.380 inches

Outside Diameter:

Between 4.570 inches and 4.620 inches

Bolt Circle Diameter:

1.750 inches

Bore Diameter:

0.748 inches

Bore Length:

0.260 inches

Drilled Hole Diameter:

0.340 inches

V Groove Angle In Deg:

36.0

Pitch Diameter:

4.500 inches

Securing Hole Quantity:

4

Material And Location:

Iron, cast, qq-i-652, class 30

Face Width:

2.300 inches

Design Form:

Webbed

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

4

Counterbore Feature:

Not included

Hole Location:

Evenly spaced on bolt circle

Keying Facility:

Not included

Securing Method:

Drilled hole

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Offset

Lightening Hole:

Included

Integral Cooling Vane:

Not included

Groove Shape:

V

Standard V-belt Section Designation For Which Designed:

A

Bore Feature:

Included

Securing Location:

Both ends

Distance From Outside Flange/rim To Hub End And Location:

1.080 inches both ends

Surface Treatment:

Phosphate coat, grade 1 special mil-c-490 enamel o.D. Per specification tt-e-529 finish

Style Designator:

Webbed or spoked

Surface Treatment:

Phosphate coat, grade 1 special mil-c-490 enamel o.D. Per specification tt-e-529 finish

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a