## NSN 3020-00-900-9589

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-900-9589

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
1.7500 inches
Teeth Quantity:
112
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thread Size:
0.086 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 plain transversely through hub, first end and 1 threaded transversely through hub, first end
Outside Diameter:
1.781 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.250 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.187 inches both ends
Hub Style Designator:
1 step first end
End Length:
0.187 inches first end
Precision Classification:
Quality number 10 or quality number 11
End Diameter:
0.500 inches first end
First Step Length:
0.063 inches first end
First Step Diameter:
0.875 inches first end
Mounting Hole Diameter:

0.046 inches transversely through hub, first end

## NSN 3020-00-900-9589

Spur Gear - Page 2 of 2

Mil-std (military Standard):

Mil-a-8625 spec.



Special Features:
Unthreaded hole 90 degrees from threaded hole
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, t4 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 1 military specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300