NSN 3020-00-901-4443



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-901-4443 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: Between 0.3430 inches and 0.3437 inches **Teeth Quantity:** 22 **Bore Style:** Plain first end **Mounting Hole Thread Series Designator:** Unc axially through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 axially through hub, first end **Mounting Hole Thread Size:** 0.086 inches axially through hub, first end **Mounting Hole Type And Quantity:** 1 threaded axially through hub, first end Nominallength: 0.375 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.250 inches first end **Face Width:** 0.125 inches **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.312 inches first end **Precision Classification:** Quality number 12 **Special Features:** Outside diameter 0.3735min 0.375max in.; bore provision included; bore diameter 0.1873min 0.1876max in.; bore length 0.375 in.; first end distance from end of hub to center of tapped hole 0.12 in.; circular pitch 0.04909 in.

Material:

Steel comp 303

Material Specification:

Qq-s-764, type 303, cond a federal specification single material response

Surface Treatment:

Passivate

NSN 3020-00-901-4443

Spur Gear - Page 2 of 2



Style Designator:	
-------------------	--

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300