NSN 3020-00-902-1612



Sprocket Wheel - Page 1 of 3 View Online at https://aerobasegroup.com/nsn/3020-00-902-1612 **Outside Diameter:** 2.814 inches **Overall Length:** 0.875 inches **Keyway Width:** 0.191 inches **Thread Size:** 1/4-20 **Bore Diameter:** Between 0.875 inches and 0.878 inches **Bore Length:** 0.875 inches **Distance From Center Of Bore To Bottom Of Keyway:** 0.534 inches **Pitch Diameter:** 2.563 inches **Securing Hole Quantity: Furnished Items And Quantity:** 1 setscrew Face Width: 0.284 inches Guide: Not included **Design Form:** Plain **Bore Type:** Straight **Counterbore Feature:** Not included **Lubrication Mode:** No visible means **Hole Location:** Lovated on top of key **Keying Facility:** Included **Keying Facility Type:**

Keyway **Securing Method:** Threaded hole

Lightening Hole:

Not included

NSN 3020-00-902-1612 Sprocket Wheel - Page 2 of 3



Protruding Hub Characteristic:
Plain
Securing Location:
Aa end
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
1
Teeth Quantity Per Row:
16
Asa Standard Chain Number:
40
Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.500 inches
Hub End Outside Diameter And Location:
2.000 inches both ends
Distance From Outside Flange/rim To Hub End And Location:
0.591 inches both ends
Material:
Steel
Material:
Steel
Quantity:
1
Surface Treatment:
Cadmium
Style Designator:
Plain
Surface Treatment:
Cadmium plated
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 3020-00-902-1612 Sprocket Wheel - Page 3 of 3



Fiig:

Т353-с