

NSN 3020-00-902-1613 Sprocket Wheel - Page 1 of 3 View Online at https://aerobasegroup.com/nsn/3020-00-902-1613 **Outside Diameter:** 4.418 inches

Overall Length:
1.000 inches
Keyway Width:
0.315 inches
Thread Size:
5/16-18
Bore Diameter:
Between 1.126 inches and 1.128 inches
Bore Length:
1.000 inches
Distance From Center Of Bore To Bottom Of Keyway:
0.722 inches
Pitch Diameter:
4.148 inches
Securing Hole Quantity:
1
Furnished Items And Quantity:
Setscrew 1
Face Width:
0.284 inches
Guide:
Guide: Not included
Not included
Not included Design Form:
Not included Design Form: Plain
Not included Design Form: Plain Bore Type:
Not included Design Form: Plain Bore Type: Straight
Not included Design Form: Plain Bore Type: Straight Counterbore Feature:
Not included Design Form: Plain Bore Type: Straight Counterbore Feature: Not included
Not included Design Form: Plain Bore Type: Straight Counterbore Feature: Not included Lubrication Mode:
Not included Design Form: Plain Bore Type: Straight Counterbore Feature: Not included Lubrication Mode: No visible means
Not included Design Form: Plain Bore Type: Straight Counterbore Feature: Not included Lubrication Mode: No visible means Hole Location:
Not included Design Form: Plain Bore Type: Straight Counterbore Feature: Not included Lubrication Mode: No visible means Hole Location: Located 90 degrees from keyway
Not included Design Form: Plain Bore Type: Straight Counterbore Feature: Not included Lubrication Mode: No visible means Hole Location: Located 90 degrees from keyway Keying Facility:
Not included Design Form: Plain Bore Type: Straight Counterbore Feature: Not included Lubrication Mode: No visible means Hole Location: Located 90 degrees from keyway Keying Facility: Included
Not included Design Form: Plain Bore Type: Straight Counterbore Feature: Not included Lubrication Mode: No visible means Hole Location: Located 90 degrees from keyway Keying Facility: Included Keying Facility Type:
Not included Design Form: Plain Bore Type: Straight Counterbore Feature: Not included Lubrication Mode: No visible means Hole Location: Located 90 degrees from keyway Keying Facility: Included Keying Facility Type: Keyway
Not included Design Form: Plain Bore Type: Straight Counterbore Feature: Not included Lubrication Mode: No visible means Hole Location: Located 90 degrees from keyway Keying Facility: Included Keying Facility Type: Keyway Securing Method:

NSN 3020-00-902-1613 Sprocket Wheel - Page 2 of 3



Protruding Hub Characteristic:
Plain
Securing Location:
Aa end
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
1
Teeth Quantity Per Row:
26
Asa Standard Chain Number:
40
Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.500 inches
Hub End Outside Diameter And Location:
2.500 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.716 inches aa end
Material:
Steel
Material:
Steel
Quantity:
1
Surface Treatment:
Paint
Style Designator:
Plain
Surface Treatment:
Painted
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 3020-00-902-1613 Sprocket Wheel - Page 3 of 3



Fiig:

Т353-с