## NSN 3020-00-903-2150

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-903-2150

## **Body Style:**

Plain, solid

#### **Pitch Diameter:**

2.8125 inches

## Teeth Quantity:

90

## Bore Style:

Plain both ends

## Backlash Designation:

Grade c

## **Outside Diameter:**

2.875 inches

## Nominallength:

0.360 inches

#### **Tooth Form:**

Standard

## Pressure Angle:

20.0000 degrees

## Distance Between Body Face And Protruding Hub End:

0.240 inches first end

## Face Width:

0.120 inches

## Bore Diameter:

0.249 inches both ends

#### Bore Depth:

0.360 inches both ends

#### Hub Style Designator:

Plain first end

#### Hub Diameter:

0.500 inches first end

#### **Precision Classification:**

Quality number 10

#### Material:

Aluminum alloy 2024

## Material Specification:

Qq-a-225/6, alloy 2024, t4 federal specification single material response

## Surface Treatment:

Anodize

#### **Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

## Style Designator:

Protruding hub

# NSN 3020-00-903-2150

Spur Gear - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

## Mil-std (military Standard):

Mil-a-8625 spec.

