# NSN 3020-00-904-4023

Spur Gear - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3020-00-904-4023

Plain, solid

**Attachment Method:** 

Mounting hole

## Pitch Diameter:

0.4380 inches

## Teeth Quantity:

14

Bore Style:

Plain first end

### Mounting Hole Type And Quantity:

1 plain transversely through hub, first end

### Nominallength:

0.750 inches

**Tooth Form:** 

Standard

## Pressure Angle:

14.5000 degrees

## Distance Between Body Face And Protruding Hub End:

0.562 inches first end

## Face Width:

0.188 inches

### Hub Style Designator:

Pinned first end

### **Special Features:**

Outside diameter 0.498min 0.5max in.; mtg hole diameter 0.125min 0.129max in.; bore provision included; bore diameter 0.2501min 0.2506max in.; bore length 0.75 in.; hub diameter 0.347min 0.3475max in.; first end distance from end of hub to center of tapped hole

0.125 in.; circular pitch 0.09818 in.

### Material:

Nickel alloy and copper alloy

### **Material Specification:**

Qq-n-281, class a, nickel-copper alloy federal specification single material response

### Style Designator:

Protruding hub

#### Shelf Life:

N/a

### Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A27300