NSN 3020-00-904-7326

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-904-7326

Body Style: Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 1.3541 inches **Teeth Quantity:** 65 **Bore Style:** Plain both ends **Backlash Designation:** Grade c **Mounting Hole Thread Series Designator:** Unc axially through body, first end **Mounting Hole Thread Size:** 0.112 inches axially through body, first end **Mounting Hole Type And Quantity:** 3 threaded axially through body, first end **Outside Diameter:** 1.396 inches **Tooth Form:** Standard Pressure Angle: 14.5000 degrees **Distance Between Body Face And Protruding Hub End:** 0.328 inches first end **Face Width:** 0.250 inches **Bore Diameter:** 0.313 inches both ends **Hub Style Designator:** Plain second end **Hub Diameter:** 0.625 inches second end **End Length:** 0.266 inches first end **Precision Classification:** Quality number 10 **End Diameter:** 0.625 inches first end First Step Length:

0.062 inches first end

NSN 3020-00-904-7326

Spur Gear - Page 2 of 2

Fiig: A27300



First Step Diameter:
1.250 inches first end
Bolt Hole Circle Diameter:
1.000 inches axially through body, first end
Material:
Copper alloy
Material Specification:
Qq-b-750, comp b, hard federal specification single material response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No