NSN 3020-00-904-7326

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-904-7326

| Pody Style |
|--|
| Body Style: Plain, solid |
| Attachment Method: |
| |
| Mounting hole |
| Pitch Diameter: |
| 1.3541 inches |
| Teeth Quantity: |
| 65 |
| Bore Style: |
| Plain both ends |
| Backlash Designation: |
| Grade c |
| Mounting Hole Thread Series Designator: |
| Unc axially through body, first end |
| Mounting Hole Thread Size: |
| 0.112 inches axially through body, first end |
| Mounting Hole Type And Quantity: |
| 3 threaded axially through body, first end |
| Outside Diameter: |
| 1.396 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 14.5000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.328 inches first end |
| Face Width: |
| 0.250 inches |
| Bore Diameter: |
| 0.313 inches both ends |
| Hub Style Designator: |
| Plain second end |
| Hub Diameter: |
| 0.625 inches second end |
| End Length: |
| 0.266 inches first end |
| Precision Classification: |
| Quality number 10 |
| End Diameter: |
| 0.625 inches first end |
| First Step Length: |
| 0.062 inches first end |
| |

NSN 3020-00-904-7326

Spur Gear - Page 2 of 2



First Step Diameter:

1.250 inches first end

Bolt Hole Circle Diameter:

1.000 inches axially through body, first end

Material:

Copper alloy

Material Specification:

Qq-b-750, comp b, hard federal specification single material response

Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300