NSN 3020-00-904-7343



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-904-7343 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: Between 1.3531 inches and 1.3541 inches **Teeth Quantity:** 65 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end **Hardness Rating:** 28.0 rockwell c and 32.0 rockwell c **Mounting Hole Thread Size:** 0.112 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 1.394 inches Nominallength: 0.328 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.235 inches first end **Face Width:** 0.093 inches **Bore Diameter:** 0.187 inches both ends **Bore Depth:** 0.328 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.375 inches first end

Precision Classification:

Quality number 10 or quality number 11

NSN 3020-00-904-7343 Spur Gear - Page 2 of 2

No Fiig: A27300



Special Features:
Distance from first end of hub to center of tapped hole 0.142 nom in.
Material:
Steel comp 416
Material Specification:
Qq-s-764, type 416, cond t federal specification single material response
Surface Treatment:
Passivate
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: