NSN 3020-00-904-7379

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-904-7379

Body Style:				
Plain, solid				
Attachment Method:				
Mounting hole				
Pitch Diameter:				
4.0000 inches				
Teeth Quantity:				
128				
Bore Style:				
Plain both ends				
Backlash Designation:				
Grade c				
Mounting Hole Thread Series Designator:				
Unf axially through body, first end				
Mounting Hole Thread Size:				
0.190 inches axially through body, first end				
Mounting Hole Type And Quantity:				
3 threaded axially through body, first end				
Outside Diameter:				
4.061 inches				
Tooth Form:				
Standard				
Pressure Angle:				
20.0000 degrees				
Distance Between Body Face And Protruding Hub End:				
0.422 inches first end				
Face Width:				
0.250 inches				
Bore Diameter:				
2.250 inches both ends				
Hub Style Designator:				
1 step first end				
End Length:				
0.234 inches first end				
Precision Classification:				
Quality number 10				
End Diameter:				
2.999 inches first end				
First Step Length:				
0.187 inches first end				
First Step Diameter:				

3.125 inches first end

NSN 3020-00-904-7379

Spur Gear - Page 2 of 2



Bolt	Hole	Circle	Diameter:
------	------	--------	-----------

3.500 inches axially through body, first end

Special Features:

Eight thd holes, no.8/0.164 in.-32 thd size equally spaced tapped 0.375 in.Deep on hub end on a 2.625 in.Dia bolt circle

Material:

Steel comp 303

Material Specification:

Qq-s-764, cond a federal specification single material response

Surface Treatment:

Passivate

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300