## NSN 3020-00-904-7390

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-904-7390

Body Style:
Plain, solid
Attachment Method:
Clamp
Pitch Diameter:
1.8750 inches
Teeth Quantity:
120
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Outside Diameter:
1.906 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.175 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.186 inches both ends
Hub Style Designator:
Plain first end
Hub Diameter:
0.280 inches first end
Precision Classification:
Quality number 10
Special Features:
Two holes 0.109 in. Dia, 0.120 in.Deep on 0.375 in.Bolt circle on second end
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, t4 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Style Designator:

Protruding hub

## NSN 3020-00-904-7390

Spur Gear - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A27300	

Mil-std (military Standard):

Mil-a-8625 spec.

Shelf Life: