NSN 3020-00-904-7391

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-904-7391

| Body Style: |
|---|
| Plain, solid |
| Attachment Method: |
| Clamp |
| Pitch Diameter: |
| 1.7500 inches |
| Teeth Quantity: |
| 112 |
| Bore Style: |
| Plain both ends |
| Backlash Designation: |
| Grade c |
| Outside Diameter: |
| 1.781 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.175 inches first end |
| Face Width: |
| 0.125 inches |
| Bore Diameter: |
| 0.186 inches both ends |
| Hub Style Designator: |
| Plain first end |
| Hub Diameter: |
| 0.280 inches first end |
| Precision Classification: |
| Quality number 10 |
| Special Features: |
| Two holes 0.109 in.Dia, 0.120 in.Deep on 0.375 in.Bolt circle on second end |
| Material: |
| Aluminum alloy 2024 |
| Material Specification: |
| Qq-a-225/6, t4 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625 military specification single treatment response |
| Style Designator: |

Protruding hub

NSN 3020-00-904-7391

Spur Gear - Page 2 of 2



| She | lf I | Life: |
|-----|------|-------|
| | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.